

Type		PMC2000	PMC3000	PMC4000	PMC5000	PMC6000	PMC9000
Max. Output torque	[Nm]	20.000	30.000	40.000	55.000	62.000	90.000
Max. input speed	[rpm]	3.500	3.500	3.500	3.000	3.000	3.000
Available ratios	1:	67 to 137	65 to 141	67 to 145	90 to 170	90 to 170	82 to 170
Weight	[kg]	100	165	180	270	280	340

Brake

Braking input torque	[Nm]	300	330	400	500	500	500
Minimum release pressure	[bar]	12	12	11	12	12	12
Maximum release pressure	[bar]	50	50	50	50	50	50

Hydraulic motor

Displacement	[cc]	32 to 50	32 to 63	63 to 90	80 to 107	80 to 107	107 to 160
--------------	------	----------	----------	----------	-----------	-----------	------------

Dimensions

L1	[mm]	115	82	111	104	104	130
L2	[mm]	201	240	236	283	283	318
L3	[mm]	331	342	347	425	425	468
D1	[mm]	280	320	350	410	410	460
D2	[mm]	330	380	400	455	455	510
D3	[mm]	370	410	435	490	490	550
D4	[mm]	235	240	240	290	290	420
D5	[mm]	270	285	285	325	325	460
D6	[mm]	330	384	374	426	426	500
D7	[mm]	N°18 M16x2	N°20 M16x2	N°18 M20	N°24 M20x2,5	N°24 M20x2,5	N°24 M20x2,5
D8	[mm]	N°18 M16	N°17 M20x2,5	N°20 M20	N°24 M20x2,5	N°24 M20x2,5	N°24 M20x2,5

